



Dimensions

Part No.	A	B	C
W-850	2.04"	2.76"	15°
V-120	2.47"	3.46"	15°
T-285	2.88"	3.91"	15°
N-175	3.15"	4.72"	15°

U.S. Trade Mark 2,898,519

Grip Range		W-850 Heavy Duty		V-120 Heavy Duty	
Inch	MM	Round/Hex	Square	Round/Hex	Square
.23 - .35	6 - 9	W850-RX-MM70	W850-S-MM98	V120-RX-MN70	V120-S-MN98
.35 - .47	9 - 12	W850-RX-MM71	W850-S-MM99	V120-RX-MN71	V120-S-MN99
.47 - .59	12 - 15	W850-RX-MM72	W850-S-MM100	V120-RX-MN72	V120-S-MN100
.59 - .70	15 - 18	W850-RX-MM73	W850-S-MM101	V120-RX-MN73	V120-S-MN101
.70 - .82	18 - 21	W850-RX-MM74	W850-S-MM102	V120-RX-MN74	V120-S-MN102
.82 - .94	21 - 24	W850-RX-MM75	W850-S-MM103	V120-RX-MN75	V120-S-MN103
.94 - 1.06	24 - 27	W850-RX-MM76	W850-S-MM104	V120-RX-MN76	V120-S-MN104
1.06 - 1.18	27 - 30	W850-RX-MM77	W850-S-MM105	V120-RX-MN77	V120-S-MN105
1.18 - 1.30	30 - 33	W850-RX-MM78	-	V120-RX-MN78	V120-S-MN106
1.30 - 1.41	33 - 36	W850-RX-MM79	-	V120-RX-MN79	V120-S-MN107
1.41 - 1.53	36 - 39	W850-R-MM13*	-	V120-RX-MN80	V120-S-MN108
1.53 - 1.65	39 - 42	W850-R-MM14*	-	V120-RX-MN81	-
1.65 - 1.77	42 - 45	-	-	V120-RX-MN82	-
1.77 - 1.89	45 - 48	-	-	V120-RX-MN83	-
1.89 - 2.00	48 - 51	-	-	V120-RX-MN84	-
2.00 - 2.12	51 - 54	-	-	V120-R-MN18*	-

*Round only

Grip Range		T-285 Heavy Duty		N-175 Heavy Duty	
Inch	MM	Round/Hex	Square	Round/Hex	Square
.47 - .59	12 - 15	T285-RX-MP72	T285-S-MP100	N175-RX-MR72	N175-S-MR100
.59 - .70	15 - 18	T285-RX-MP73	T285-S-MP101	N175-RX-MR73	N175-S-MR101
.70 - .82	18 - 21	T285-RX-MP74	T285-S-MP102	N175-RX-MR74	N175-S-MR102
.82 - .94	21 - 24	T285-RX-MP75	T285-S-MP103	N175-RX-MR75	N175-S-MR103
.94 - 1.06	24 - 27	T285-RX-MP76	T285-S-MP104	N175-RX-MR76	N175-S-MR104
1.06 - 1.18	27 - 30	T285-RX-MP77	T285-S-MP105	N175-RX-MR77	N175-S-MR105
1.18 - 1.30	30 - 33	T285-RX-MP78	T285-S-MP106	N175-RX-MR78	N175-S-MR106
1.30 - 1.41	33 - 36	T285-RX-MP79	T285-S-MP107	N175-RX-MR79	N175-S-MR107
1.41 - 1.53	36 - 39	T285-RX-MP80	T285-S-MP108	N175-RX-MR80	N175-S-MR108
1.53 - 1.65	39 - 42	T285-RX-MP81	T285-S-MP109	N175-RX-MR81	N175-S-MR109
1.65 - 1.77	42 - 45	T285-RX-MP82	T285-S-MP110	N175-RX-MR82	N175-S-MR110
1.77 - 1.89	45 - 48	T285-RX-MP83	-	N175-RX-MR83	N175-S-MR111
1.89 - 2.00	48 - 51	T285-RX-MP84	-	N175-RX-MR84	N175-S-MR112
2.00 - 2.12	51 - 54	T285-RX-MP85	-	N175-RX-MR85	N175-S-MR113
2.12 - 2.24	54 - 57	T285-RX-MP86	-	N175-RX-MR86	-
2.24 - 2.36	57 - 60	T285-RX-MP87	-	N175-RX-MR87	-
2.36 - 2.46	60 - 63	T285-R-MP21*	-	N175-RX-MR88	-
2.46 - 2.59	63 - 66	-	-	N175-RX-MR89	-
2.59 - 2.71	66 - 69	-	-	N175-RX-MR90	-
2.71 - 2.83	69 - 72	-	-	N175-RX-MR24*	-
2.71 - 2.83	72 - 75	-	-	N175-RX-MR25*	-
2.83 - 3.07	75 - 78	-	-	N175-RX-MR26*	-

*Round only

See page 34 for Accuracy Chart